

TECHNICAL DATA SHEET

Part#: 7248E

Cutters - Medium Taper Relieved Head - Laser Flush - Short Handle
Designed for cutting .036" soft wire leaving no 'pinch' on the wire

The 7248E Lazer Line[®] medium tapered/relieved laser flush cutter has a cutting capacity of .001" - .036" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. The CNC machining allows the joint surfaces to be perfect to allow for long life. The dual leaf springs provide a smooth action. It features an ergonomically molded antimicrobial Anti-Static grip (10¹⁰ ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10 ¹⁰ ohms/sq
• Shape	Taper Relieved Head
• Type of Cut	Lazer Flush
• Cutting Capacity	.001 - .036"
• Blade Angle	14.25°
• Blade Length	.36" (9mm)
• Body Width	0.42" (10.5mm)
• Body Height	.25"
• OAL	4.75" (118.75mm)
• Weight (OZ)	3
• UPC	662847009587
• Schedule B	8203.20.60.60
• ECCN	EAR99
• UNSPSC Code	27111511
• Country of Origin	USA
• Group	Medium Cutters - 7000 Series

